

TERRA 180° SWING BARRIER



The manual bi-directional HVM Swing Barrier has been successfully impact tested to the International IWA 14 specification with 7.2t @ 48kph (30mph). Maximum width 10,000mm.

- IWA 14 Terra 180° Swing Barrier 7.2t @ 48kph
- V/7200[N2A]/48/90:1.7

Tested dimensions: width 6000mm, crash beam height 942mm

worldofesf.com

E sales@worldofesf.com
 T UK +44 (0) 2890 364 101
 US 1-888-601-6444



Environmental Street Furniture
 Valley Business Centre
 67 Church Road
 Newtownabbey
 Belfast, BT36 7LS



ESF
Secure

BENEFITS & FEATURES

- Successfully impact tested to the new International IWA 14-1 specification
- The Bi-directional, Lightweight HVM Gate which is easy to install and easy to operate
- Sleek design includes an impact beam which can be opened in either direction depending on site requirements
- The ideal solution for access points which need to be secured with occasional access, out of hours security, or remote locations with power supply restrictions
- Anti-tamper locking mechanism
- Secure apertures up to 10,000mm
- Shallow embedment depths of only 350mm required. Foundation depth of only 500mm
Foundation Type B

CIVIL REQUIREMENTS

Gate base (millimetres)

L: 1600 x W: 1200 x E: 350

Receptor post foundations (millimetres)

L: 1600 x W: 1200 x E: 350

Foundation Depth 500mm

- * This is subject to a risk assessment to ensure the automatic equipment complies to BS EN 12453



worldofesf.com

E sales@worldofesf.com

T UK +44 (0) 2890 364 101

US 1-888-601-6444



ISO
9001 : 2015
REGISTERED



fsb[®]



Irish Security
Industry Association

Environmental Street Furniture
Valley Business Centre
67 Church Road
Newtownabbey
Belfast, BT36 7LS



Company No. NI 615794

VAT GB 153402248